



TYPE	ASPIRATO	PERFORATO	GRIGIA	SPUNGE	SPUNGE
GRS	1.8	2.1	-10	+120	115
SGO-D	2.3	2.1	-10	+120	115
SGO-E	2.7	2.2	-10	+120	115
SGO-E nc	2.7	2.2	-10	+120	115
SGO-M	2.2	2.3	-10	+120	115
GRS-S	2.5	2.6	-10	+120	115
SG1	2.0	2.6	-10	+120	115
SG1-E	3.0	2.3	-10	+120	115
SG3	2.0	2.2	-10	+120	100
LHP	1.8	2.1	-10	+120	115
SG5	2.0	1.8	-10	+120	100
SG6	2.0	2.3	-10	+120	100
SG7	2.0	2.2	-10	+120	115
SG7 gr	2.0	2.2	-10	+120	115
SG7-H	2.0	2.2	-10	+120	115
EHB	1.7	2.0	-10	+120	115
SG7-M	1.9	1.3	-10	+120	115
SG7-S	2.5	2.9	-10	+120	115
SG8	2.0	2.1	-10	+120	100
SG8 HX	2.5	2.1	-10	+120	100
LHB	1.7	2.0	-10	+120	115



TYPE	ASPIRATO	PERFORATO	GRIGIA	SPUNGE	SPUNGE
NG0	1.5	1.6	0	+100	100
NG3	2.0	2.2	0	+100	100
NG5	1.9	2.1	0	+100	100
NG7	1.7	1.9	0	+100	115
NG7-S	2.5	2.6	0	+100	115
NG8	2.0	2.0	0	+100	100
NET	3.5	0.7	-40	+70	50
LK	1.8	2.0	0	+60	100
PV5 BIANCO	2.3	2.4	0	+60	100
GK	1.9	2.0	0	+60	100
LKV	1.8	2.0	0	+60	100
GKV	1.9	2.0	0	+60	100
SID	1.1	1.0	-20	+160	115
SID-FG	1.4	1.3	-50	+200	115
HTL	1.5	1.4	-50	+200	115
SI1ez	1.6	1.7	-20	+150	115
HTE	1.5	1.4	-50	+200	115
BF	2.4	0.8	-10	+60	50
GRIP	2.0	0.9	-20	+110	100
LGH	1.6	2.1	-20	+120	100
FT3	3.0	1.1	-20	+100	55